Serial No. 10/753,288

AMENDMENT TO THE SPECIFICATION

Please amend the entire paragraph [0011], as shown in the following Marked-Up Version of the replacement paragraph:

--Firstly, refer to the modified examples of gardening scissors in the present invention, as shown in Figures 1, 2 and 3. Available with force plate construction, this The gardening scissor is normally comprised of two handles 10, a fixed jaw 11, a movable jaw 12 and a linkage slab 13 as well as a module board 14. The fixed jaw 11 and module board 14 are constructed of two separating boards A and B [[available in]] with a seam C between them.--

Please amend the entire abstract on page 5, as shown in the following Marked-Up Version of the replacement abstract:

--A gardening scissor includes a handle, a fixed jaw, a movable jaw, a linkage slab, and a module board. The fixed jaw and module board are constructed of two separating boards [[available in]] with a seam between them. The seam is provided with a protective cover by the hood. The width of this hood is capable of [[proving]] providing a cover on the seam, provided that the flexibility of fixed jaw and movable jaw is not hindered. The linkage side of hood is available with a built-in edge. Besides, the built-in edge and the inwall between two boards are provided with a bulge strip and notch for positioning of the hood. It is possible to prevent branches inserting into the seam and enrich the appearance of gardening scissors.--